



dla srub bez kontry po regulacji
uzyc WEICONLOCK AN 302-50 | after regulation use WEICONLOCK AN 302-50 for screws without selflocking

8Nm

9 podciecie od wewnatrz | undercut from the inside

7Nm

11 podciecie od gory i wewnatrz**** | undercut from the inside and the top****

8Nm

dla kata 6 stopni umiescic element 14 pomiedzy el. 2 a el. 8 | for the camber 6 degrees put part 14 between parts 2 and 8

**** - dla kol off road i kata 2 stopnie podciecia od dolu i zewnatrz | for the off road wheels and camber 2 deg. undercuts from the outside and the bottom

Exploded Trigo Left Rear Wheel with Clamps

Plan No.

EP00243/L

Scale: 1:4

Drafted

Verified

Confirmed

Date

16/10/2017

06/02/2025

06/02/2025

Initials

AS

PM

AS



EP00243 / L

Material TRIGO			
No.	Plan	Article	Quantity
1	XP01582	GP08199	1
2	XP01583	GP08899	1
**	XP03257(0°-2°)	GP26699	1
**	XP03262(4°-6°)	GP26799	1
3	XP01373	GP08399	1
4	XP01372	GP08299	1
5	XP01374	GP08499	1
6	XP01375	GP08599	1
7	XP01695	GP111	1
**	XP03258	GP268	1
8	M16 DIN17222	1911653	1
9	M6x20DIN912	2994004	4
10	M6X12DIN912	2994005	1
11	M5x40ISO 7379	2994002	2
12	M5black	2994006	2
13	M5 DIN125	2994069	2
14	XP02299	GP16700	1
15	M16	1992699	1
16	Quickrelease D12 -113	1915500	1
17*	20"BLACK AIR SRR	1914845	1
	BLACK AIR SMP	1914846	1
	22"BLACK AIR SRR	1914847	1
	BLACK AIR SMP	1914848	1
	24"BLACK AIR SRR	1914849	1
	BLACK AIR SMP	1914850	1
	PU BLACK	1916185	1
	26"BLACK AIR SRR	1914851	1
	BLACK AIR SMP	1914852	1

Material TRIGO			
No.	Plan	Article	Quantity
16	Quickrelease D12 -123	1915471	1
17*	18" KID AIR SMR	2990955	1
	24"SPIRIT ALU AIR SRR	1914876	1
	SPIRIT ALU AIR SMP	1914877	1
	SPIRIT RED AIR SRR	1914878	1
	SPIRIT RED AIR SMP	1914879	1
	SPIRIT BLUE AIR SRR	1914880	1
	SPIRIT BLUE AIR SMP	1914881	1
	OFF ROAD AIR	2990958	1
16	Quickrelease D12.7	2990034	1
17*	24"SPINERGY AIR SMP	2990957	1
	SPINERGY AIR SRR	1914882	1
18	Washer M6- black	2994414	2
19***	XP03259 (B330A)	2994885	1
	XP03260 (B330)	2994884	1
20	TRIGO GREY	T001145	1
	TRIGO RED	T001146	1
	TRIGO BLUE	T001147	1



* for depths 32-36 use only 18" and 20" wheels
 use corresponding quickrelease
 ** only for spinergy wheels
 *** option for 24" wheels
 **** for the off road wheels and camber 2 deg.
 undercut from the outside and the bottom

EP00243/L

Exploded Trigo Left Rear Wheel with Clamps				Plan No.
Page 2/2				EP00243/L
Scale: 1:4	Drafted	Verified	Confirmed	
Date	16/10/2017	06/02/2025	06/02/2025	
Initials	AS	PM	AS	